



VENTO AIR

_Refrigerated shelves. Ready to connect

Fast, flexible and effective

VENTO AIR are air-cooled refrigerated shelves with integrated air condenser. All components required for operation are already installed in the refrigerated cabinet, allowing universal placement even in the middle of the room. This version allows quick and easy installation in the store, even without closing the store if necessary.



VISUAL MERCHANDISING

VENTO AIR are a completely flexible and connectable family of refrigerated shelves designed for high product loads. With a wide range of glass door designs, VENTO AIR is ideally suited for optimum product presentation.



LOW COSTS

The low investment outlay and operating costs speak for themselves. In addition, the VENTO AIR scores with minimum maintenance costs. The integrated and energy-efficient LED head lighting and optional shelf lighting ensure optimum presentation of your goods.



FLEXIBLE SYSTEM

The industrially manufactured refrigeration circuits of the VENTO AIR offer the lowest risk of leakage.



COMPATIBLE WITH THE ACTIVE MONITORING SYSTEM

Our Active Monitoring System (AMS) allows us to detect problems before you notice them. As an essential add-on to all AHT products, the AMS makes it much easier for you to manage and monitor the AHT cooling systems in your stores. Our products are also compatible with other systems.



ENVIRONMENT AND CLIMATE

VENTO AIR operate with a hermetically sealed cooling system and use the ecologically harmless and natural refrigerant propane (R290). This makes them particularly environmentally friendly.

INDIVIDUAL BRANDING

VENTO refrigerated cabinets can be individually adapted to the store design. A wide range of colours allows the best possible integration.



TEMPERATURE RANGES

H1 – Chilled vegetables & fruit	33.8F to 50F
M2 – Dairy products	30.2F to 44.6F
M1 – Dairy products, colder	30.2F to 41F
M0* – Dairy products, special temp.	30.2F to 39.2F
S1* – Meat & fish	30.2F to 25.6F

* with GD models only

BENEFITS

ENERGY EFFICIENCY BENCHMARK

With the VENTO AIR GD ECO, AHT has the most energy-efficient multi-deck refrigeration unit on the market. The single refrigerant circuit, hinged glass doors and optimised seals allow enormous energy savings to be achieved.

FLEXIBLE PLACEMENT & INSTALLATION

The VENTO AIR can be easily connected to an existing Multideck system. Thanks to very easy installation, several shelves can also be added to an existing shelf system in next to no time. No expensive machine room is needed, because all the necessary components are already installed in the Multideck.



Versions



VENTO AIR GD ECO

VENTO AIR GD ECO operates with just one compressor and its optimised seals make it one of the most energy-efficient glass-door refrigerated cabinets on the market – perfect for minimising your CO₂ footprint.

VENTO AIR GD

VENTO AIR is also available with hinged doors made of glass or plastic. Sliding glass doors are also available. These add-ons make the VENTO more energy efficient, and thus contribute to cutting your energy costs.

A large selection of glass door versions for individual design can be found in the accessories catalogue.



VENTO AIR

VENTO AIR comprises a wide range of air-cooled cabinets and is operated with the natural refrigerant R290.

CONFIGURATIONS

Stand-alone



In-line



Block



Island*





_ optionally with end cabinet on both sides

_ specific installation, per type on request

*except H8 models



VENTO AIR



Symbolic image

DIMENSIONS

VENTO AIR		Width	Height	Depth	Shelf depth
EC LS6	inches	70.07	86.61	37.44	23.62
LS6	inches	70.07	86.61	37.44	23.62
LS6	inches	98.42	86.61	37.44	23.62
LS6	inches	147.63	86.61	37.44	23.62
EC LS6 ECO*	inches	70.07	86.61	37.44	23.62
LS6 ECO*	inches	70.07	86.61	37.44	23.62
LS6 ECO*	inches	98.42	86.61	37.44	23.62
LS6 ECO*	inches	147.63	86.61	37.44	23.62
EC HS6 ECO*	inches	70.07	94.48	37.44	31.49
HS6 ECO*	inches	70.07	94.48	37.44	23.62
HS6 ECO*	inches	98.42	94.48	37.44	23.62
HS6 ECO*	inches	147.63	94.48	37.44	23.62
L8	inches	49.21	94.48	49.68	31.49
L8	inches	98.42	94.48	49.68	31.49
L8	inches	147.63	94.48	49.68	31.49
L8 ECO*	inches	98.42	94.48	49.68	31.49
L8 ECO*	inches	147.63	94.48	49.68	31.49
LC L8**	inches	98.42	92.51	49.68	31.49
LC L8**	inches	147.63	92.51	49.68	31.49
LB H8***	inches	98.42	94.48	49.68	31.49
LB H8***	inches	98.42	94.48	49.68	31.49
H8	inches	98.42	94.48	49.68	31.49
H8	inches	147.63	94.48	49.68	31.49
H8 ECO*	inches	98.42	94.48	49.68	31.49
H8 ECO*	inches	147.63	94.48	49.68	31.49

* With glass doors only ** Skirt height 400mm – Electrical components under the refrigerated shelf *** Low front – skirt height 220 mm
 Number of glass swing doors: EC 178/178 – 3 doors, 250 – 4 doors, 375 – 6 doors, irrespective of type
 Further data can be found in the data sheet of the Ecodesign Directive (2009/125/EC).

Subject to technical changes; errors and omissions excepted. Version: 03/2022



AHT Cooling Systems

7058 Weber Blvd
 Ladson, SC 29456

phone: +1 843 767 6855

sales@us.aht.at
 www.us.aht.at