

## Technical data

### Multi-mode cabinet (R,F,IC)\*

# MONTREAL SLIM PUSH 250 (U) NAM

**R-290    110-120V/60Hz**

<b>General data</b>		Refrigerator IAT**	Freezer IAT**	Ice cream freezer IAT**
gross content	Liter	1233		
net content	Liter	510	654	702
total display area (TDA)	m <sup>2</sup>	1,67		
classification acc. to 10 CFR §431 Subpart C - Commercial Refrigerators, Freezers and Refrigerator-Freezers	---	R	F	ICF
ambient temperature range	°C ... °C	+16 ... +25		
adjustment temperature range	°C ... °C	-2,2 ... +8,3	-19 ... -13	-30 ... -21
sound pressure in 1 m distance	dB(A)	43,6		
<b>Electrical data</b>				
nominal voltage/frequency	V / Hz	110-120/60		
nominal power consumption cabinet	W	450		
nominal current	A	9,0		
fuse protection	A	15		
energy consumption (at 24°C)	kWh/24 h	2,80	4,54	8,15
length of power supply cord	mm	1750		
<b>Refrigeration data</b>				
refrigerant type	---	R-290		
refrigerant charge	g	120		
max. operating pressure	bar	30		
<b>Physical dimensions</b>				
length outside/inside	mm	2503 / 2373		
depth outside/inside	mm	887 / 723		
front access height/height outside	mm	846 / 910		
height inside	mm	735		
stacking height (is basket height for meat cooling)	mm	360	470	470 / 530
net weight (excl. packaging, incl. internal accessories necessary for meat cooling)	kg	199		
gross weight (incl. packaging, incl. internal accessories necessary for meat cooling)	kg	235		

\*Multi-mode cabinet: Temperature setting from -22°F to +47°F possible,

\*\*IAT - Integrated Average Temperature

## Technical data

### Multi-mode cabinet (R,F,IC)\*

# MONTREAL SLIM PUSH 250 (U) NAM

**R-290    110-120V/60Hz**

<b>General data</b>		<b>Refrigerator IAT**</b>	<b>Freezer IAT**</b>	<b>Ice cream freezer IAT**</b>
gross content	cu.ft.	43,53		
net content	cu.ft.	18,01	23,10	24,79
total display area (TDA)	sq.ft.	17,98		
classification acc. to 10 CFR §431 Subpart C - Commercial Refrigerators, Freezers and Refrigerator-Freezers	---	R	F	ICF
ambient temperature range	°F ... °F	61 ... 77		
adjustment temperature range	°F ... °F	+28 ... +47	-2,2 ... +8,6	-22 ... -5,8
sound pressure in 1 m distance	dB(A)	43,6		
<b>Electrical data</b>				
nominal voltage/frequency	V / Hz	110-120/60		
nominal power consumption cabinet	W	450		
nominal current	A	9,0		
fuse protection	A	15		
energy consumption (at 75.2°F)	kWh/24h	2,80	4,54	8,15
energy consumption (at 75.2°F)	BTU/24h	9554	15491	27809
length of power supply cord	inch	68,9		
<b>Refrigeration data</b>				
refrigerant type	---	R-290		
refrigerant charge	oz	4,23		
max. operating pressure	bar	30		
<b>Physical dimensions</b>				
length outside/inside	inch	98,54 / 93,43		
depth outside/inside	inch	34,92 / 28,46		
front access height/height outside	inch	33,31 / 35,83		
height inside	inch	28,94		
stacking height (is basket height for meat cooling)	inch	14,17	18,50	18,5 / 20,87
net weight (excl. packaging, incl. internal accessories necessary for meat cooling)	lb	439		
gross weight (incl. packaging, incl. internal accessories necessary for meat cooling)	lb	518		

\*Multi-mode cabinet: Temperature setting from -22°F to +47°F possible,

\*\*IAT - Integrated Average Temperature

Adjustment temperature range has to be chosen according to product requirements

24.08.2021